Process and Resource Simulations

What

- Determined critical workpiece features
- Calculated surface error
 - End milling of multi-step pocket
 - Face milling of top surface
- Predicted drill torque and thrust in metering hole


Why

- Identify improvements to the process plan and fixture design before committing to the shop floor
- Reduce shop floor rework

How


Performed simulations in a networked collaborative environment

"Manufacturing in a Computer"






Distributed Enterprise Process and Resource Simulation



TEAM

Technologies Enabling Agile Manufacturing

Material Removal Simulations



Face Milling Simulations

- Detailed analysis of surface error from finish face milling operation on top surface
- Investigate alternative manufacturing plans to reduce surface error
 - Fixture designs
 - » 3-2-1 fixture design
 - » 4-clamp fixture design
 - Process plans

How

- Generated 3-D IGES representation of part using ProEngineer
- Developed 3-D finite element mesh with I-DEAS
- Computed stiffness matrix and influence coefficients using ABAQUS
- Calculated surface error due to workpiece deformation with FMSIM
- Results used in Process and Resource Tradeoff


Process Simulations Reduce Shop Floor Rework




Face Milling Surface Error Calculation Process

3-D Wireframe IGES Representation from ProEngineer

3-D Finite Element Mesh Developed with I-DEAS









Face Milling Surface Error

Workpiece Displacement from ABAQUS

Surface Error Calculated with FMSIM






Improve Fixture Design and Process Plan Before Committing to the Shop Floor



FACE MILLING SIMULATIONS OF TEAM PART



Technologies Enabling Agile Manufacturing





End Milling Simulations

 Detailed analysis of surface error from end milling operation in multi-step pocket

- EMSIM analysis via the Internet
- Results used in product and process tradeoff

Wall Surface Error Due to End Mill Deflection







Larger diameter end mill reduces surface error, but affects product



Drilling Simulations

- Analysis of drill torque and thrust during drilling operation in metering hole
- Investigated range of hole diameters from 4 20 mm





Process Simulations used for Global Tradeoff

